



Durable Labels that Last

320 Durable White "VOID" Polyester

Description: This tamper-evident polyester has a ultra-smooth topcoat for fine resolution printing. Only when someone tries to remove this label, will its special, aggressive adhesive leave behind a distinct and highly visible "VOID" message. If security slits are added to the label, it will tear when lifted.

Common uses include asset tracking and warranty tracking in the automotive, electronics and pharmaceutical markets.

Compliance: RoHS and REACH SVHC Candidate List dated December 19, 2012
UL Recognized for Marking & Labeling Systems PDGQ2. See EIM File #MH48554 for UV Inkjet printed labels.

Recommended Printing Ribbons: EIM T84/T85, T80/T81 and T96/T97 Resins

	Face Stock	Adhesive	Liner
Type	Polyester	Permanent "VOID" Acrylic*	Kraft Paper
Color	White	-	-
Caliper	2.1 mil (53 micron) +/-10%	0.7-0.8 mil (18-20 microns) +/- 10%	3.1 mil (79 micron) +/- 10%
Basis or Coat Weight	-	-	50#
Min. Application Temp	-	50°F (10°C)	-
Exterior Life	-	Two Years*	-
Service Temp. Range	-	-40°F to 302°F (-40°C to 150°C)*	-

* **NOTES:** Please allow 24-48 hours for your labels to setup before testing for tamper evidence. The tamper evident features of this product will become permanently non-functional if it is exposed to temperatures above 104°F (40°C). Additionally, if this material is used outside, the white coating may turn yellow with extended exposure to sunlight.

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F (21°C)	50% R.H.	Two Years

All descriptive information, typical performance data, and recommendations for this product should be used solely as a guide. Furnishing such information is merely our attempt to assist you as indicated by your requested application. These specifications do not constitute a warranty under any varying results. All labels are sold with the understanding that the purchaser has independently tested and determined the suitability of the product for the intended application. 041013