



Durable Labels that Last

617 Acid-Free Semi-Gloss Paper

Description: This premium, bright white paper offers excellent strength and print quality. This product would also be appropriate for retail labeling and product identification requiring a high-quality, attractive image.

It comes with a permanent adhesive that has a wide service temperature making it suitable for a large variety of applications including warm and hot filling containers, freezer storage and labeling low-surface-energy plastics. It is also glove-friendly.

The paper is alkaline-based and the adhesive has been tested to Photographic Activity (PAT) per ISO 14523, a specification that covers the pH, lignin content, tear resistance and alkaline reserve. Therefore the construction is deemed "acid-free" making it suitable for marking documents, photos and other critical items being stored and tracked.

Regulatory & Compliance (pertaining to the all-temperature adhesive):

- 21 CFR 175.105 for indirect food contact
- 21 CFR Part 801 for natural rubber content
- 16 CFR 1500.3 for oral toxicity
- 16 CFR 1500.3 (c) (4) for Primary Dermal Irritation
- CONEG / Toxics in Packaging (for heavy metal content)
- Toy Safety for heavy metal content

Recommended Printing Ribbons: To work on the hard finish on this material, our T68 Resin ribbon is recommended. You may have to use higher printer heat settings to get good results.

	Face Stock	Adhesive	Liner
Type	Paper	Permanent Acrylic	Bleached Kraft
Color	White	Clear	-
Caliper	3.1 mil	0.6 mil	2.5 mil
Basis Weight	60#/3300 ft ²	-	30.6#/3000 ft ²
Opacity	87.5%	-	64%
Brightness	89%	-	-
Gloss	75%	-	-
Tensile #/inch	35 MD/ 19 CD	-	35 MC / 15 CD
Tear grams	47 MD/ 46 CD	-	42 MC / 48 CD
Min. Application Temp.	-	-20°F (29°C)	-
Temperature Range	-	-65°F to 200°F (-54°C to 93°C)	-
Total Construction Caliper	6.2 mil		
	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F (21°C)	50% R.H.	One Year

All descriptive information, typical performance data, and recommendations for this product should be used solely as a guide. Furnishing such information is merely our attempt to assist you as indicated by your requested application. These specifications do not constitute a warranty under any varying results. All labels are sold with the understanding that the purchaser has independently tested and determined the suitability of the product for the intended application. 040710