



Durable Labels that Last

668 Freez-R-Mark™ Plastic

Description: This gloss-coated plastic has an aggressive “freezer” adhesive featuring excellent initial tack and ultimate bond to flexible packaging and varnished or waxed corrugated., even when applied at freezer temperatures. It is an excellent option for applications where the label can be applied to packaging materials at room temperature and then subjected to -40°F blast freezing. You will find it also adheres to many surfaces that have certain amounts of frost or moisture build-up and works well on highly textured surfaces. The liner is perfect for die cut labels and auto-apply applications, but is not recommended for sheeting or fan-fold formats.

Regulatory & Compliance:

21 CFR 175.105 for indirect food contact
21 CFR Part 801 for natural rubber content
CONEG for Heavy Metal

Recommended Printing Ribbons: T84 or T96 Resins for durability

	Face Stock	Adhesive	Liner
Type	Plastic	Permanent Rubber	Bleached Kraft Paper
Color	White	Clear	White
Caliper	2.6 mil	0.6 mil	2.5 mil
Basis or Coat Weight	33.2#/3000 ft ²	-	40#/3000 ft ²
Min. Application Temp	-	-15°F (-26°C)	-
Service Temp. Range	-	-65°F to 160°F (-54°C to 71°C)	-
Total Construction	5.7 mil		

	Temperature	Humidity	Shelf Life
Recommended Storage Conditions	70°F	35% to 85% R.H.	One Year

All descriptive information, typical performance data, and recommendations for this product should be used solely as a guide. Furnishing such information is merely our attempt to assist you as indicated by your requested application. These specifications do not constitute a warranty under any varying results. All labels are sold with the understanding that the purchaser has independently tested and determined the suitability of the product for the intended application.